

# FIREBULL®

## Class A Wetting Agent



FIREBULL® is manufactured by EnforcerOne, LLC.  
Contact EnforcerOne for more details at  
678-788-8413 or info@enforcerone.com  
www.enforcerone.com

### PRODUCT INFO:

Environmentally formulated FIREBULL Class A Foam is the newest generation in nonfluorinated foam. FIREBULL Class A Foam contains ZERO hazardous materials in the formulation; it will not clog, gum, or corrode foam systems and equipment. This environmentally formulated concentrate implements a dramatically changed chemistry compared to most foams. This chemistry enables FIREBULL Class A Foam to be used in all types of foam portioning systems, compressed air foam systems (CAFS), in-line eductors, and standard foam equipment.

### APPLICATIONS

Grass fires and Initial Structural  
Knockdown: 0.10% - 0.25%  
Tire Fires, Landfill Fires, Coal Fires and  
Wildland Fires:  
0.25% - 0.50%  
Car/Vehicle Fires/Overhaul/Spill Fires  
0.50% - 1.0%

### APPLICATION NOTES

Recommended to set foam  
system defaults between 0.25%  
and no more than 0.50%  
Compressed Air Foam Systems  
(CAFS) should be calibrated  
using a foaming solution under  
50 cps for accurate calibration

### FLUSHING INSTRUCTIONS

It is recommended to flush all  
Class A foam tanks if possible. If  
not, use as much of previous Class  
A foam, then add FIREBULL  
concentrate. Mixing with most  
Class A foams will not cause harm  
to systems.

### SHELF LIFE

FIREBULL Class A foam has a  
twenty year shelf-life when stored  
in sealed original containers..

### COMPATIBILITY

Compatible with other brands of  
foam as finished foam.  
Compatible with other FIREBULL  
products as a concentrate.

### PHYSICAL PROPERTIES

Appearance: Natural Amber  
PH: 7.5-8.5  
Viscosity: 20 cps  
Min. Storage Temp: 35°F (2°C)  
Max. Storage Temp: 120°F (-49°C)  
Effect of Freeze/Thaw: None



## Associated Products



**FIREBULL  
FLUORINE FREE FOAM**



**FIREBULL  
TRAINING FOAM**



**ENFORCER 30 CAFS**



**ENFORCER 10 CAFS**